



AIMgSI0.5 F22 AW6060 FLACH
 EN755-5/EN573-3

mm	mm	6 mtr	kg/mtr	mm	mm	6 mtr	kg/mtr
15	3	X	0,125	50	8	X	1,080
15	5	X	0,202	50	10	X	1,350
15	6	X	0,245	50	12	X	1,620
15	8	X	0,324	50	15	X	2,030
15	10	X	0,405	50	20	X	2,700
20	3	X	0,165	60	3	X	0,486
20	4	X	0,220	60	4	X	0,650
20	5	X	0,270	60	5	X	0,810
20	6	X	0,325	60	6	X	0,972
20	8	X	0,435	60	8	X	1,300
20	10	X	0,540	60	10	X	1,620
20	12	X	0,648	60	12	X	1,940
20	15	X	0,810	60	15	X	2,430
25	3	X	0,203	60	20	X	3,240
25	4	X	0,270	70	5	X	0,945
25	5	X	0,340	70	10	X	1,890
25	6	X	0,405	80	3	X	0,650
25	8	X	0,540	80	4	X	0,860
25	10	X	0,675	80	5	X	1,080
25	12	X	0,840	80	6	X	1,300
25	15	X	1,015	80	8	X	1,730
30	3	X	0,245	80	10	X	2,160
30	4	X	0,324	80	12	X	2,592
30	5	X	0,405	80	15	X	3,240
30	6	X	0,490	80	20	X	4,320
30	8	X	0,650	90	10	X	2,430
30	10	X	0,810	100	3	X	0,810
30	12	X	0,975	100	4	X	1,100
30	15	X	1,220	100	5	X	1,350
30	20	X	1,620	100	6	X	1,620
40	3	X	0,324	100	8	X	2,160
40	4	X	0,435	100	10	X	2,700
40	5	X	0,540	100	15	X	4,050
40	6	X	0,648	100	20	X	5,600
40	8	X	0,864	120	5	X	1,620
40	10	X	1,080	120	6	X	1,944
40	12	X	1,300	120	8	X	2,600
40	15	X	1,620	120	10	X	3,240
40	20	X	2,160	120	15	X	4,860
50	3	X	0,405	120	20	X	6,480
50	4	X	0,540	150	10	X	4,050
50	5	X	0,675	200	10	X	5,400
50	6	X	0,810				



Wir erweitern ständig unser Lagerprogramm, nicht aufgeführte Abmessungen sind auf Anfrage lieferbar.


■ AIMgSI0.5 AW6060 RUND EN755-3/EN573-3



mm	6 mtr	kg/mtr
8	X	0,140
10	X	0,212
12	X	0,305
15	X	0,480
16	X	0,543
20	X	0,850

mm	6 mtr	kg/mtr
25	X	1,320
30	X	1,910
40	X	3,390
50	X	5,300
60	X	7,630


■ AIMgSI0.5 F22 AW6060 VIERKANT EN755-4/EN573-3



mm	6 mtr	kg/mtr
8	X	0,175
10	X	0,270
12	X	0,390
15	X	0,610
20	X	1,080

mm	6 mtr	kg/mtr
25	X	1,690
30	X	2,430
40	X	4,320
50	X	6,750

■ AIMgSI0.5 F22 AW6060 U-PROFIL EN755-9/EN573-3



mm	mm	mm	6 mtr	kg/mtr
15	15	2	X	0,221
20	20	2	X	0,320
20	20	3	X	0,455
25	25	2	X	0,400
25	25	3	X	0,560
30	20	2	X	0,350
30	30	2	X	0,490
30	30	3	X	0,715
35	35	3	X	0,800

mm	mm	mm	6 mtr	kg/mtr
40	20	2	X	0,410
40	30	3	X	0,790
40	40	4	X	1,250
50	30	3	X	0,842
50	50	4	X	1,533
50	50	5	X	1,940
60	30	3	X	0,925
60	40	2,5	X	0,911
60	60	4	X	1,858

Wir erweitern ständig unser Lagerprogramm, nicht aufgeführte Abmessungen sind auf Anfrage lieferbar.


■ AIMgSI0.5 F22 AW6060 T-PROFIL EN755-9/EN573-3

mm	mm	mm	6 mtr	kg/mtr	mm	mm	mm	6 mtr	kg/mtr
20	20	2	X	0,205	40	40	4	X	0,820
25	25	3	X	0,380	50	50	5	X	1,285
30	30	3	X	0,461	60	60	4	X	1,252




■ AIMgSI0.5 F22 AW6060 WINKEL GLEICHSCH. EN755-9/EN573-3

mm	mm	mm	6 mtr	kg/mtr	mm	mm	mm	6 mtr	kg/mtr
15	15	2	X	0,151	45	45	2	X	0,480
15	15	3	X	0,220	50	50	2	X	0,531
20	20	2	X	0,205	50	50	3	X	0,785
20	20	3	X	0,299	50	50	4	X	1,040
25	25	2	X	0,259	50	50	5	X	1,290
25	25	3	X	0,380	60	60	2	X	0,637
25	25	4	X	0,500	60	60	3	X	0,950
30	30	2	X	0,313	60	60	4	X	1,252
30	30	3	X	0,465	60	60	5	X	1,552
30	30	4	X	0,604	60	60	6	X	1,850
30	30	5	X	0,742	60	60	8	X	2,420
35	35	2	X	0,370	80	80	4	X	1,685
35	35	3	X	0,545	80	80	6	X	2,500
40	40	2	X	0,423	80	80	8	X	3,283
40	40	3	X	0,650	100	100	4	X	2,110
40	40	4	X	0,824	100	100	6	X	3,140
40	40	5	X	1,015	100	100	10	X	5,200




■ AIMgSI0.5 F22 AW6060 WINKEL UNGLEICHSCH. EN755-9/EN573-3

mm	mm	mm	6 mtr	kg/mtr	mm	mm	mm	6 mtr	kg/mtr
20	10	2	X	0,151	50	30	4	X	0,821
20	15	2	X	0,178	50	30	5	X	1,027
25	10	2	X	0,180	50	40	4	X	0,929
25	15	2	X	0,205	60	20	2	X	0,425
25	20	2	X	0,235	60	30	3	X	0,704
30	15	2	X	0,232	60	30	5	X	1,163
30	20	2	X	0,260	60	40	2	X	0,530
30	20	3	X	0,380	60	40	3	X	0,785
30	20	4	X	0,500	60	40	4	X	1,040
40	15	2	X	0,290	60	40	5	X	1,285
40	20	2	X	0,315	80	30	3	X	0,900
40	20	3	X	0,461	80	40	2	X	0,655
40	20	4	X	0,604	80	40	4	X	1,253
40	30	3	X	0,545	80	40	6	X	1,850
50	20	2	X	0,370	80	60	6	X	2,171
50	20	3	X	0,545	100	30	3	X	1,027
50	30	2	X	0,426	100	50	3	X	1,200
50	30	3	X	0,625	100	50	5	X	1,958




Wir erweitern ständig unser Lagerprogramm, nicht aufgeführte Abmessungen sind auf Anfrage lieferbar.

AIMgSI0.5 F22 AW6060 QUADRATROHR EN755-8/EN573-3




mm	mm	mm	6 mtr	kg/mtr	mm	mm	mm	6 mtr	kg/mtr
15	15	2	X	0,281	50	50	2	X	1,037
20	20	2	X	0,388	50	50	3	X	1,540
20	20	3	X	0,550	50	50	4	X	1,987
25	25	2	X	0,497	60	60	2	X	1,253
25	25	3	X	0,713	60	60	3	X	1,820
30	30	2	X	0,615	60	60	4	X	2,419
30	30	3	X	0,880	80	80	3	X	2,495
35	35	2	X	0,756	80	80	4	X	3,283
40	40	2	X	0,826	100	100	3	X	3,143
40	40	3	X	1,199	100	100	4	X	4,150
40	40	4	X	1,560	100	100	5	X	5,130

AIMgSI0.5 F22 AW6060 RECHTECKROHR EN755-8/EN573-3



mm	mm	mm	6 mtr	kg/mtr	mm	mm	mm	6 mtr	kg/mtr
20	10	2	X	0,324	60	40	4	X	1,980
20	15	2	X	0,335	80	20	2	X	1,040
25	20	2	X	0,443	80	30	3	X	1,690
30	15	2	X	0,460	80	40	2	X	1,253
30	20	2	X	0,496	80	40	3	X	1,847
30	20	3	X	0,713	80	40	4	X	2,419
40	20	2	X	0,604	80	50	4	X	2,640
40	20	3	X	0,874	80	60	3	X	2,175
40	30	2	X	0,713	80	60	4	X	2,950
40	30	3	X	1,037	100	20	2	X	1,274
50	15	2	X	0,660	100	30	3	X	2,010
50	20	2	X	0,712	100	40	3	X	2,171
50	25	2	X	0,765	100	40	4	X	2,930
50	30	2	X	0,821	100	50	3	X	2,333
50	30	3	X	1,198	100	50	4	X	3,070
50	40	3	X	1,458	100	60	3	X	2,495
60	20	2	X	0,822	100	60	4	X	3,290
60	30	2	X	0,961	120	20	2	X	1,469
60	30	3	X	1,430	120	60	4	X	3,800
60	40	2	X	1,040	140	80	4	X	4,580
60	40	3	X	1,523					

AIMgSI0.5 F22 AW6060 RUNDROHR EN755-7/EN573-3




mm	mm	6 mtr	kg/mtr	mm	mm	6 mtr	kg/mtr
16	2	X	0,240	40	2	X	0,645
20	2	X	0,305	40	3	X	0,942
20	3	X	0,433	40	10	X	2,546
25	2	X	0,390	50	2	X	0,820
25	3	X	0,560	50	3	X	1,196
30	2	X	0,475	60	2	X	0,990
30	3	X	0,660	60	3	X	1,450
32	2	X	0,509	80	2	X	1,325
35	2	X	0,560	80	3	X	1,959

Wir erweitern ständig unser Lagerprogramm, nicht aufgeführte Abmessungen sind auf Anfrage lieferbar.

ALCU4PBMGMN AW2007T4 FLACH

EN755-5/EN573-3


mm	mm	3 mtr	kg/mtr	mm	mm	3 mtr	kg/mtr
20	10	X	0,560	50	40	X	5,600
20	15	X	0,840	60	10	X	1,680
25	10	X	0,700	60	15	X	2,520
25	15	X	1,050	60	20	X	3,360
25	20	X	1,400	60	30	X	4,860
30	10	X	0,840	60	40	X	6,720
30	12	X	1,000	80	10	X	2,240
30	15	X	1,260	80	12	X	2,690
30	20	X	1,680	80	15	X	3,360
30	25	X	2,100	80	20	X	4,480
40	10	X	1,120	80	30	X	6,720
40	12	X	1,340	80	40	X	8,960
40	15	X	1,680	100	10	X	2,800
40	20	X	2,240	100	12	X	3,360
40	25	X	2,800	100	15	X	4,200
40	30	X	3,360	100	20	X	5,600
50	10	X	1,400	100	30	X	8,400
50	15	X	2,100	100	40	X	11,200
50	20	X	2,800	100	50	X	14,000
50	25	X	3,375	120	20	X	6,700
50	30	X	4,200	120	30	X	10,000



ALCU4PBMGMN AW2007T4 RUND

EN755-3/EN754-3/EN573-3


mm	3 mtr	kg/mtr	mm	3 mtr	kg/mtr
6	X	0,080	65	X	9,300
8	X	0,140	70	X	10,770
10	X	0,220	75	X	12,370
12	X	0,320	80	X	14,070
15	X	0,490	85	X	15,700
16	X	0,563	90	X	17,500
20	X	0,880	95	X	21,000
25	X	1,370	100	X	21,980
28	X	1,760	110	X	26,600
30	X	1,980	120	X	31,200
32	X	2,250	130	X	37,200
35	X	2,690	140	X	43,000
40	X	3,520	150	X	48,600
45	X	4,450	160	X	56,000
50	X	5,490	180	X	72,500
55	X	6,650	200	X	87,300
60	X	7,910			



ALCU4PBMGMN AW2007T4 VIERKANT

EN754-4/EN573-3

mm	3 mtr	kg/mtr	mm	3 mtr	kg/mtr
15	X	0,630	50	X	7,000
20	X	1,120	60	X	10,100
25	X	1,750	70	X	13,700
30	X	2,520	80	X	17,900
40	X	4,480	100	X	28,000



Wir erweitern ständig unser Lagerprogramm, nicht aufgeführte Abmessungen sind auf Anfrage lieferbar.

BLECH AL99.5 AW1050A H14/H24
EN573-3/EN485-1




Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
0,8	4,400	6,800	
1,0	5,500	8,500	12,200
1,5	8,500	13,000	18,500
2,0	11,000	17,000	25,000
2,5	13,500	21,500	30,500
3,0	16,500	25,500	37,000
4,0	22,000	34,000	50,000
5,0	27,000	43,000	61,000

BLECH AL99.5 AW1050A H14/H24 EINSEITIG FOLIERT
EN573-3/EN485-1



Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
1,5	8,500	13,000	18,500
2,0	11,000	17,000	25,000
3,0	16,500	25,500	37,000

BLECH AlMg1 AW5005 H14/H24
BANDELOX. E6/EV1 EINSEITIG FOLIERT




Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
2	11,000	17,000	25,000

Wir erweitern ständig unser Lagerprogramm, nicht aufgeführte Abmessungen sind auf Anfrage lieferbar.


■ **BLECH AlMg3 AW5754 H22**
EN573-3/EN485-1

Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
1,0	5,500	8,500	12,200
1,5	8,500	13,000	18,500
2,0	11,000	17,000	25,000
2,5	13,500	21,500	30,500
3,0	16,500	25,500	37,000
4,0	22,000	34,000	50,000
5,0	27,000	43,000	61,000



■ **BLECH AlMg3 AW5754 H111**
EN485-3/EN573-3

Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
6,0	33,000	51,000	73,000
8,0	44,000	68,000	98,000
10,0	56,000	87,000	126,000




■ **BLECH AlMg3 AW5754 H22 EINSEITIG FOLIERT**
EN573-3/EN485-1

Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
1,5	8,500	13,000	18,500
2,0	11,000	17,000	25,000
3,0	16,500	25,500	37,000



DUETT-WARZENBLECH AIMg3 AW5754
EN1386/EN573-3



Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
1,5/2,0	9,000	14,000	20,000
2,5/4,0	15,500	24,000	34,500
3,5/5,0	21,000	32,500	47,000
5,0/6,5	29,000	45,000	65,000
8,0/9,5	46,000	71,000	102,000

QUINTETT-WARZENBLECH AIMg3 AW5754
EN1386/EN573-3



Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
2,5/4,0	16,000	24,500	35,000
3,5/5,0	21,500	33,000	47,500
5,0/6,5	29,500	45,500	66,000

Wir erweitern ständig unser Lagerprogramm, nicht aufgeführte Abmessungen sind auf Anfrage lieferbar.